




Coastal's MacroCTDs

- Description:** Coastal's MacroCTDs and MacroCTDs+ are the ideal instruments to monitor and record conductivity, temperature, and depth for salinity and speed of sound calculations.
- Capacity:** 200K standard
Optional (Compact Flash Cards): 8MB, 16MB, etc.
- Housing:** **Diameter** – 5.5 in.
Length – 19.5 in. (including handle)
Weight – 18 lbs. in air
Material – Stainless steel and UHMW plastic housing
- Power:** User replaceable standard alkaline D cells
- Interface:** Wizard IBM PC compatible software
ASCII data files in engineering units
User controlled sampling parameters and sensor functions
- Clock:** Solid state real time, accuracy one minute per year
- Standard:** **Conductivity, Inductive** – Falmouth Scientific C-T Sensor
Pressure, Standard – ICS Strain Gauge
Temperature, External – YSI Thermister
- Optional:** **Conductivity, High Precision** - Seabird SBE-4
Standard for MacroCTDs+ **Pressure, High Precision** - Paroscientific Digiquartz
Temperature, High Precision - Seabird SBE-3



Coastal MacroCTDs



FSI C-T Sensor

Function	Sensor (*optional)	Range	Accuracy	Resolution	Units
Conductivity, Inductive	FSI OEM CT Sensor	0->64	0.025	0.018	mmho/cm
Pressure, Standard	IC Sensors Strain Gauge, piezoresistive	30, 50, 100, 250	0.1%	12 bit	psia
Temperature	YSI Ext. Bulkhead Thermister	-5° to 35°	0.1°	.02 typ	°C
Conductivity, High Precision	*SeaBird SBE-4 Conductivity Sensor	0-70	0.003	0.001	mmho/cm
Pressure, High Precision	*Paroscientific Digiquartz	900<	0.015%	16 bit	psia
Temperature, High Precision	*SeaBird SBE-3 Temperature	-5° to 35°	.004°	16 bit	°C